

JNR20S series

Diameter	Model No.	Resistance at 25°C (Ω)	Thermal dissipation coefficient (mW/°C)	Thermal Time constant (S)	I <sub>max</sub> (A)	Maximum Capacitance AC240V (uF)	Rated Temperature TL~TU(°C)
20D	20S0R7M	0.7	≥18	≤220	13.0	1000	-40~+200
	20S0R7L	0.7			13.0		
	20S1R0M	1			13.0		
	20S1R0L	1			13.0		
	20S1R3M	1.3			10.0		
	20S1R3L	1.3			10.0		
	20S1R5M	1.5			10.5		
	20S1R5L	1.5			10.5		
	20S2R0M	2			10.0		
	20S2R0L	2			10.0		
	20S2R2M	2.2			9.5		
	20S2R2L	2.2			9.5		
	20S2R5M	2.5			9.0		
	20S2R5L	2.5			9.0		
	20S030M	3			8.5		
	20S030L	3			8.5		
	20S040M	4			8.0		
	20S040L	4			8.0		
	20S4R7M	4.7			7.5		
	20S4R7L	4.7			7.5		
	20S050M	5			7.5		
20S050L	5	7.5					
20S060L	6	7.0					
20S6R8L	6.8	6.5					
20S070L	7	6.5					

20S080L	8
20S100L	10.0
20S120L	12
20S130L	13
20S150L	15.0
20S160L	16.0
20S180L	18.0
20S200L	20.0
20S121L	120

6.0	
6.0	
5.0	
5.0	
4.5	
4.5	
4.0	
4.0	
2.0	1500