

40X40X15 mm

KF0415-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)		
KF0415B5SR	B	5	4.25~5.75	10.32	0.325	8600	0.53	2.65	0.70	39.0	25		
KF0415B5HR				8.84	0.237	7300	0.32	1.60	0.44	32.9			
KF0415-5M	B, S			7.14	0.159	6000	0.21	1.05	0.25	28.6			
KF0415-5L	B, S			5.70	0.113	5000	0.16	0.80	0.17	24.9			
KF0415B1SRAR	B	12	10.2~13.8	14.94	0.537	12200	0.23	2.76	0.25	53.1			
KF0415B1SR				10.32	0.325	8600	0.19	2.28	0.25	39.0			
KF0415B1HR	8.84			0.237	7300	0.13	1.56	0.17	32.9				
KF0415-1M	B, S			7.14	0.159	6000	0.08	0.96	0.11	28.6			
KF0415-1L	B, S			5.70	0.113	5000	0.06	0.72	0.08	24.9			
KF0415B2SRAN	B			24	20.4~27.6	11.05	0.435	10000	0.09	2.16		0.11	45.6
KF0415B2SR						10.32	0.325	8600	0.09	2.16		0.11	39.0
KF0415B2HR	8.84					0.237	7300	0.07	1.68	0.08		32.9	
KF0415-2M	B, S	7.14	0.159			6000	0.05	1.20	0.06	28.6			
KF0415-2L	B, S	5.70	0.113			5000	0.03	0.72	0.04	24.9			

Specifications subject to change without notice

The 7th character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

