



## ■ 技术参数 SPECIFICATIONS

- 线数 (Poles) : 2、3、4、6、8、9
- 适用线规 (Applicable wires) : AWG24#~16#
- 适应基板厚度 (Applicable PC board thickness) : 1.6mm
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 300V.Ac/Dc
- 额定电流 (Current rating) : 9A max
- 接触电阻 (Contact resistance) :  $\leq 0.015\Omega$
- 绝缘电阻 (Insulation resistance) :  $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 1500V.Ac/1min
- 材料 (Material) :
  - 插头 (Plug housing) : 尼龙 (Nylon) UL94V-2(0)
  - 插座 (Receptacle housing) : 尼龙 (Nylon) UL94V-2(0)
  - 插片 (Retainer) : 尼龙 (Nylon) UL94V-2
  - 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)

### 端子 TERMINAL(39612)

型号 Type	适用线规 Applicable wires		电线外径 O.D of wire ins mm	数量 Quantity
	mm <sup>2</sup>	AWG#		
HX39612-21PT	0.51~1.38	20~16	1.8~3.1	3500PCS/盘
HX39612-01PT	0.2~0.52	24~20	1.5~1.9	4000PCS/盘

型号 Type	适用线规 Applicable wires		电线外径 O.D of wire ins mm	数量 Quantity
	mm <sup>2</sup>	AWG#		
HX39612-21RT	0.51~1.38	20~16	1.8~3.1	3500PCS/盘
HX39612-01RT	0.2~0.52	24~20	1.5~1.9	4000PCS/盘

线数 (Poles)	额定电压 (Voltage rating)	额定电流 (Current rating)	HX39612-PT(177915-1)	HX39612-RT(177917-1)	插片(Retainer)
			插头 (Plug housing)	插座 (Receptacle housing)	
2	300V	9A	HX39612-2P(177898-1)	HX39612-2R(179463-1)	HX39612-2S(177918-1)
			HX39612-3P(177899-1)	HX39612-3R(179464-1)	HX39612-3S(177919-1)
			HX39612-4P(177900-1)	HX39612-4R(179465-1)	HX39612-2S(177918-1)